

GEKKOTEX is a Self Adhesive Polyester Fabric that can be installed on virtually any surface and then removed and reused many times over. The adhesion will not leave a residue on the surface when it's removed. GEKKOTEX is revolutionizing the marketplace when it comes to dressing public and commercial spaces. GEKKOTEX the easiest way to change the visual appeal of a space. From cafes, bars and restaurants to high-street retail stores... the market and creative possibilities with GEKKOTEX are as wide as your own imagination!

Material Description

Quality	100% Self Adhesive Woven Polyester Fabric		
Material	Polyester		
Thickness	150 mic	ASTM D645	
Weight	97 g/m ²	ASTM 646	
Total Thickness	335 mic		
Peel Strength (180°, kgf/2.54cm)	20min	0.7 ≤ 0.78	ASTM D903
	24 h	0.9 ≤ 1.02	ASTM D903
Holding Power	Minute	60 ≤	ASTM D3654 at 60C
Tensile Strength (kgf/mm ²)	MD	45 ≤ 50.4	ASTM D882 (Except Release Paper)
	TD	35 ≤ 40.4	ASTM D882 (Except Release Paper)

Physical Properties

- Semi-matte surface
- Denier: 150D x 150D
- core: 3"
- standard length: 30m
- standard width: 1270mm & 1370mm
- 90g PE coated paperadhesive on the back side, acryl based (weak and strong adhesive)

Compatibility

Eco Solvent	✓
Solvent	✓
Latex	✓
UV-curable	✓
UV-curable Led	✓
Water	✓
Oil	✓
Dye-sublimation	—

Printing guidelines

Max. temperature (material) should not exceed 80°C as overheating can impair the flatness of the media. Ink restrictions and heater settings have to be set for specific printer ink combinations to obtain the best results.

Make your own practical test to be sure it reaches your quality standard.
For all- and latest information see our Compatibility List.

Product information

September 2011



Qualifications

150 mic



Applications

- Wall Covering
- Stand building
- Indoor decoration

The possibilities and opportunities are endless...!



Storage conditions

1 year under normal conditions (10–25°C at a relative humidity of 30–75 %). Higher humidity and/or temperature can affect the product performance. Always store the media in a dark place.



Environment

The media and final prints can be disposed of as paper waste. Material is suitable for recycling. Please consult local recycle resources. For treatment of ink or ink residue, please refer to your printer manual or supplier.

Colour profiles

TEPEDE develops high quality ICC colour profiles for the divers printing media's. We work with specialists that can do this service for almost every printer - rip combination

- Hewlett Packard
- Epson
- Mutoh
- Mimaki
- Roland
- And more...